

# XTeer COMP-P VG 68, 100

## Description

XTeer COMP-P is an extraordinary Compressor Oil. It is formulated with excellent quality base oil technology and a high technology additive system that assures exceptional equipment protection and reliability for compressors operating. It is especially designed to provide excellent wear protection and outstanding resistance to oxidation and thermal. Furthermore, it shows the ability to help reduce maintenance costs through minimizing equipment problems and downstream deposits and carryover.

## Application

Recommended for continuous high temperature operation

- Specifically recommended for reciprocating air compressor
- Units operating under severe conditions

## Features / Benefits

- Oxidation Stability
- Low Evaporation Loss
- Antifoam Properties
- Rust Protection

## Remarks

XTeer COMP-P meets or exceeds the requirements of

- SIEMENS TLV 9013 04
- SIEMENS TLV 9013 05
- ALSTOM HTGD 90117 W0001
- GENERAL ELECTRIC GEK-32568J
- DIN 51515 Part 1, 2

XTeer COMP-P VG	Density (15°C, kg/m <sup>3</sup> )	Viscosity		Viscosity Index	Flash Point (°C)	Pour Point (°C)
		40°C	100°C			
68	820	72.99	9.47	107	240	-30
100	876	108.4	12.26	104	246	-35