

XTeer TOP PRIME 5W40

Description

XTeer TOP PRIME is a premium performance engine oil formulated with state of the art additives and fully synthetic base fluids. It provides best thermal and oxidative stability for improved oil life and deposit control as well as excellent friction reduction and seal compatibility enhancement. XTeer TOP PRIME is fully suitable for use in gasoline passenger car, light duty gasoline truck, diesel passenger car and LPG passenger car under all operating conditions. The wider temperature range capability of the synthetic base fluid ensures correct oil viscosity which reduces friction at start-up and provides maximum lubrication during high temperature operation in all seasons. The effective anti-wear additive system reduces wear by protecting surfaces when load causes breakdown of the lubricant film.

Application

- Gasoline/Diesel Compact/LPG cars
- Prestige cars like BMW/BENZ/LEXUS
- DPF / CPF – installed cars
- High fuel efficiency – featured cars
- High accelerator reaction speed – demanded cars

Features / Benefits

- It provides maximum engine protection at the highest speeds
- It maximizes the engine performance in the toughest conditions Low foaming
- It reduces deposit and sludge in turbocharged engines by more than 50%
- It reduces deposit and sludge in engines and pistons
- Tested with all rubber seals in the engine

Remarks

XTeer TOP PRIME meets or exceeds the requirements of

- API SN/CF
- ACEA C3, A3/B3/B4
- MB-Approval 229.31/229.51
- Renault RN0700/RN0710
- BMW Longlife – 04
- GM dexos 2
- Porsche A40
- Ford WSS-M2C917-A
- VW 502 00/505 00/505 01

SAE	Viscosity		Viscosity Index	Flash Point (°C)	Pour Point (°C)
	40°C	100°C			
5W40	84.33	14	172	222	-35